


Type:



- Fully assembled housing is formed and welded, 20 ga. steel, chemically treated to resist corrosion and enhance paint adhesion
- Model variations offered for surface, cable suspended and pendant mount applications
- Available in standard white, black, silver, platinum, bronze and primer powder coat, applied post production (consult factory for custom finishes)
- Includes frosted or linear prismatic acrylic lens
- Available for T8 17W, 25W, 32W, and 40W linear fluorescent lamps in single and some tandem lengths
- Standard ballast is specification grade 120V-277V program start (consult factory for other voltage options)
- Dimming, emergency battery backup and specialized ballast factor options available (consult factory for availability and system compatibility)
- Knock-outs on back accept standard electrical fittings by others (consult factory for other locations)
- Rotational locking lamp holders
- UL and C-UL listed for dry and damp locations
- IBEW manufactured and labeled
- Made in the U.S.A.

IPR8R +

Watts W	Voltage ⚡	Ballast 📦	Lens 👁️	Mount 🏠	Finish 🎨
Section 1	Section 2	Section 3*	Section 4	Section 5	Section 6
<ul style="list-style-type: none"> 17W: 24" 25W: 36" 32W: 48" 40W: 60" 	<ul style="list-style-type: none"> U: 120V-277V 347: 347V CF: consult factory for specialized voltage 	<p>[Non-Dimming]</p> <ul style="list-style-type: none"> IS: instant start <p>[Dimming]</p> <ul style="list-style-type: none"> H300: Lutron Hi-Lume 3D H317: Lutron Hi-Lume 3D ESYS: Lutron EcoSystem EHD: Lutron EcoSystem H DALI: Dali T8 	<p>[Emergency]</p> <ul style="list-style-type: none"> I28: Iota ISL-28 I54: Iota ISL-54 I540: Iota ISL-540 L50: Bodine LP500 L55: Bodine LP550 L60: Bodine LP600 L60S: Bodine LP600STU LB51: Bodine B50LP 	<ul style="list-style-type: none"> F: frosted P: linear prismatic 	<ul style="list-style-type: none"> SM: surface mount CM48: cable mount 48" cable length CM96: cable mount 96" cable length PM18: pendant mount 18" stem length PM24: pendant mount 24" stem length PM30: pendant mount 30" stem length CF: consult factory for custom length
					<ul style="list-style-type: none"> WH: white BL: black SL: silver PT: platinum BZ: bronze PR: primer CF: consult factory for custom color

*Not all ballasts work with all lamps. Consult factory for details.

