

BSS110 | QuickShip Information

Adjustable linear LED cove mount fixture

Project: _____ Type: _____



QuickShip

- Review all Bartco Lighting QuickShip Terms and Conditions.
- Provide a purchase order or completed QuickShip Order Form to our Customer Service Department. If you are sending a PO, please note clearly that it is a QuickShip order.
- Only include QuickShip items on your QuickShip order. Available options are designated on the QuickShip Order Form, any fixture ordered that is not designated on the QuickShip Order Form will be processed separately as a normal order, with a normal lead-time.
- Double check to ensure complete and correct QuickShip catalog numbers are provided or simply add quantity requirements to our convenient QuickShip Order Form.
- Include complete shipping and contact information.
- Limit QuickShip quantities to 50 pieces or fewer per fixture type per order.
- No changes or cancellations can be made once the Sales Order Confirmation has been sent.
- Send your purchase order by email with "QuickShip" in the subject line, or email or fax a completed QuickShip Order Form to customerservice@bartcolighting.com or 714-230-3222 (fax).

SPECIFICATIONS

Fixture mounting/wiring channel is formed and welded 20 ga. steel chemically treated to resist corrosion and enhance paint adhesion.

LED housing is extruded aluminum with sheet aluminum end caps.

Standard fixture finish is semi-gloss white powder coat, applied post production

Includes frosted acrylic lens for wide angle diffusion

Available in nominal lengths of 2', 3', 4' and 5'

LED housing rotates and locks in place without tools at -15°, 0°, 15°, 30°, 45°, 60°, 75°, 90° and 105°

Knock outs on ends, and underside accept standard electrical fittings by others

Standard integral 120V-277V driver offered with 0-10V dimming (cap dimming leads in the field for non-dimming operation)

Standard output is 625 lumens per foot

LEDs available in 3000K and 3500K, within a 3 step MacAdam ellipse, all with 90+ CRI typical

LED life rated at 50,000 hours

Limited five year warranty


UL and C-UL listed for dry and damp locations

IBEW manufactured and assembled

MADE IN U.S.A.

LENGTH / MOUNTING DIMENSIONS

ORDERING CODE	LENGTH
	A
2	23-3/32"
3	34-9/32"
4	45-7/16"



PERFORMANCE

NOMINAL LENGTH	OUTPUT	LUMENS/ft.	WATTS/ft.	LUMINAIRE LUMENS	EFFICACY (LPW)
4'	R: regular	625	7.7	2362	81

*Note: All data reflects fixtures with 3500K LEDs

BSS110 -

<p>FIXTURE LENGTH</p> <p>2: 23-3/32"</p> <p>3: 34-9/32"</p> <p>4: 45-7/16"</p>	-	<p>CORRELATED COLOR TEMPERATURE</p> <p>30: 3000K - 90+ CRI</p> <p>35: 3500K - 90+ CRI</p>	-	<p>D</p> <p>DRIVER</p> <p>[Dimming]</p> <p>D: 0-10V, 1% (cap dimming leads in the field for non-dim operation)</p>	-	<p>R</p> <p>LIGHT OUTPUT</p> <p>(lumens per foot)</p> <p>R: regular - 625</p>	-	<p>F</p> <p>LENS</p> <p>F: frosted</p>
--	---	---	---	---	---	--	---	---