

2" wide rectilinear LED luminaire for outdoor locations and remote driver operation

Project: _____ Type: _____



FEATURES

The BSW208 is a linear LED luminaire for outdoor applications. The surface mount 2" wide by 3" tall extrusion is fitted with a flush, frosted lens and machined aluminum end caps. Each fixture is paired with a remote mounted wet location 0-10V dimming or non-dimming driver and housing.

SPECIFICATIONS

Fixture constructed of an extruded aluminum housing, extruded, frosted acrylic lens and machined aluminum end caps

Standard finishes as shown below

Available for surface mounting in nominal lengths of 2'-8' single fixtures and continuous runs

Continuous run fixtures provided with 18 ga. wet location cable for powering up to XXAmps of

Fixtures wired with 10' low voltage leads

Included remote 120-277V wet location driver offered with 0-10V dimming or non-dim and surface mount aluminum enclosure

Performance data pending lab tests


LEDs available in 3000K, 3500K and 4000K, within a 3 step MacAdam ellipse, all with 80+ CRI typical

Life: 50,000 hours L70

Limited five year warranty

UL and C-UL listed for wet locations

SECTION



BSW208 -


NOMINAL FIXTURE LENGTH*	CORRELATED COLOR TEMPERATURE	DRIVER [remote]	LIGHT OUTPUT (lumens per foot)	MOUNT	RUN CONFIGURATION	FINISH
2: 23-3/4"	30: 3000K-80+ CRI	RN: non-dimming	L: low	SM: surface mount	SN: single	AW: architectural white (semi-matte)
3: 35-1/8"	35: 3500K-80+ CRI	RD: 0-10V dimming, 5%	R: regular	CF: consult factory for custom mounting	ST: starter	WH: white (semi-gloss)
4: 46-5/8"	40: 4000K-80+ CRI		H: high		AD: adder	BL: black (semi-matte)
5: 58"					TR: terminator	MB: matte black
6: 69-3/8"						ESS: environmental satin silver
7: 80-3/4"						BZ: bronze
8: 92-1/8"						PR: primer
						CF: consult factory for custom finish

Note: Each fixture includes a remote driver matched for fixture length and light output
 * Actual dimension dependent on run configuration

MOUNTING

ORDERING CODE

DESCRIPTION



SM

SURFACE MOUNT

- Use appropriate fastener through Ø3/16" holes in housing
- 10' low voltage leads exit out the rear at an end

EPA CALCULATIONS

LENGTH ORDERING CODE	EPA
2	0.99 ft ²
3	1.46 ft ²
4	1.94 ft ²
5	2.42 ft ²
6	2.89 ft ²
7	3.36 ft ²
8	3.84 ft ²