

BHR300 | HORIZON

3-3/8" square illuminated coffer luminaire



Project: _____ Type: _____



FEATURES

The Horizon BHR300 linear illuminated coffer luminaire provides clean, understated yet high performance general illumination. Housed in a 3-3/8" square extrusion, a visibly quiet, 2" wide illuminated coffer distributes light efficiently across a broad range. Surface and cable mounting options are available, as well as a variety of dimming drivers and light outputs, to maximize the versatility of this clean design luminaire.

SPECIFICATIONS

Fixture constructed of an extruded aluminum housing, chassis, and machined aluminum end caps

Model variations offered for surface and cable suspended applications

Coffer formed of 98% reflective material

Standard finishes as shown below

Available in nominal lengths of 2'-7' single fixtures and continuous runs

Basic continuous run fixtures provided with 18 ga. wiring harness for 6 Amp maximum load (consult factory for runs requiring multiple circuits, sensor integration, etc.)

LED modules, driver, and reflector are integrated into the chassis, which snaps into the outer housing for simple and quick installation

Standard integral 120-277V driver offered with 0-10V dimming or non-dim (other dimming driver options available)

Integral 120-277V emergency battery backup available for 4' nominal non-dim or 0-10V (consult factory for all other lengths/drivers)

Standard light outputs are 665 and 880 lumens per foot


LEDs available in 2700K, 3000K, 3500K, and 4000K, within a 3 step MacAdam ellipse, all with 90+ CRI typical

Life: 50,000 hours L₇₀

Limited five year warranty

UL listing pending

SECTIONS



PERFORMANCE

NOMINAL LENGTH	OUTPUT	LUMENS/ft.	WATTS/ft.	LUMINAIRE LUMENS	EFFICACY
4'	L: low	665	6.8	2450	97
	R: regular	880	9.0	3251	98

Note: All data reflects fixtures with 3500K LEDs



BHR300 -

NOMINAL FIXTURE LENGTH*

- 23: 22-11/16"
- 36: 35-3/4"
- 49: 49-1/4"
- 62: 62-5/16"
- 71: 71"
- 84: 84-5/16"

CORRELATED COLOR TEMPERATURE

- 27: 2700K-90+ CRI
- 30: 3000K-90+ CRI
- 35: 3500K-90+ CRI
- 40: 4000K-90+ CRI

DRIVER

- ND: non-dimming
- [Dimming]**
- D: 0-10V, 1%
- HE: Lutron EcoSystem, 1%
- HES: Lutron EcoSystem, soft-on fade-to-black, 1%
- H2: Lutron Hi-lume 2-wire forward phase, 1%, (120V ONLY)
- E5: Lutron EcoSystem 5-Series, 5%
- EL: eldoLED ECOdrive 0-10V, 1%

LIGHT OUTPUT (lumens per foot)

- L: low - 665
- R: regular - 880
- CF: consult factory for custom output

MOUNT

- SM: surface mount
- C4: cable mount 4' cable length
- C8: cable mount 8' cable length
- CF: consult factory for custom mounting

RUN CONFIGURATION

- SN: single
- ST: starter
- AD: adder
- TR: terminator

END TREATMENT (for SN, ST, TR)

- A: solid square end cap
- B: arched flat end cap

OPTIONS



- ED: emergency driver (49" non-dim or 0-10V fixtures only)
- WS1: Wattstopper FS-205 ‡
- ES1: EasySense SN102 ‡
- ES2: EasySense SN200 ‡
- ES3: EasySense SN300 ‡
- EN1: Enlighted FS-D22 ‡

FINISH

- AW: architectural white (semi-matte)
- WH: white (semi-gloss)
- BL: black (semi-matte)
- MB: matte black
- ESS: environmental satin silver
- BZ: bronze
- PR: primer
- CF: consult factory for custom finish
- SA: satin anodize (may require additional lead time)

* Actual dimension dependent on run configuration
 ‡ See sensor section for driver compatibility information

MOUNTING

	ORDERING CODE	DESCRIPTION
	SM	<p>SURFACE MOUNT</p> <ul style="list-style-type: none"> • Use appropriate fastener through Ø3/16" holes in housing
 <p>C4 = 48" Nom. C8 = 96" Nom.</p>	C4 and C8	<p>CABLE MOUNT</p> <p>Mounting option includes:</p> <ul style="list-style-type: none"> • Ø 1/16" x 48" (C4) or 96" (C8) aircraft cables • 60" (C4) or 108" (C8) power cable (in coordinating finish) • Bracket bars • Ø 5" white canopies • Ceiling couplers • Cable grippers

END TREATMENT

Note: These options apply to SN, ST and TR configuration fixtures

	ORDERING CODE	DESCRIPTION	SPECIFICATION
	A	SOLID SQUARE CAP	1/4" thick, square machined aluminum end cap
	B	ARCHED OPENING CAP	1/4" thick machined aluminum end cap with arched opening

OPTIONS

ORDERING CODE	DESCRIPTION	SPECIFICATIONS
ED	EMERGENCY LED DRIVER	<ul style="list-style-type: none"> • Universal 120-277V input voltage emergency driver delivers initial minimum power of 10W for 90 minutes • Available for 4' nominal length non-dim or 0-10V fixture only (consult factory for all other lengths/drivers)

INTEGRATED SENSORS

Note: Sensor options add 3-1/2" to the overall fixture length.

ORDERING CODE	BRAND AND MODEL	FUNCTIONS	
WS1	Wattstopper FS-205	Occupancy and light level sensor	For use with on/off or 0-10V dimming drivers only
EN1	Enlighted FS-D22	Occupancy, ambient light sensing, daylight harvesting, and environment monitoring for Enlighted control network	Provided with Advance sensor ready series 0-10V dimming drivers
ES1	Philips EasySense SN102	Occupancy, daylight harvesting and task tuning sensor with simple grouping	Provided with Advance sensor ready series 0-10V dimming drivers
ES2	Philips EasySense SN200	Occupancy, daylight harvesting and task tuning sensor with advance grouping	
ES3	Philips EasySense SN300	Occupancy, daylight harvesting sensor for integration with Zigbee control networks	